



## 160° Wide Angle 2MP Panoramic Dome IR Camera

### Feature:

SONY 1/2.9" CMOS 2MP Chip

Coaxial cable, RJ45 twisted network wire transmission

UTC function

AHD/TVI/CVI or Analog 960H Video Output selectable

Built-in IR-Cut filter lens, more accurate Day/Night co-focus

3D/2D noise reduction.

NTSC/ PAL selectable

Support Digital-WDR

ShineTech Electronics Co., Ltd.

Address: No. 169, Anji Street, Zuoying District, Kaohsiung City

Factory: 9th Floor, No. 93, Dashun 1st Road, Zuoying District, Kaohsiung City

TEL:886-7-5585859 FAX:886-7-5585860 Email:Shinotech@shinotech.com.tw

Model: SSV-XHD-535S30

|                                           |                                                    |
|-------------------------------------------|----------------------------------------------------|
| Pick-up Element                           | SONY 1/2.9 "CMOS IMX 323V30H                       |
| Frame Rate                                | 1080P@25fps / 1080P@30fps                          |
| Lens                                      | 1.8mm Fisheye Lens                                 |
| Effective Pixel                           | 1920(H)×1080(V)                                    |
| Standard                                  | PAL/NTSC                                           |
| Day/Night Mode                            | External(Default) / Auto / Color / B&W             |
| Video Setting                             | Contrast/Sharpness/COLOR/GAIN/DNR/Format/DWDR      |
| White Balance                             | ATW/Manual                                         |
| Synchronization                           | Internal                                           |
| Electronic Shutter                        | Auto                                               |
| Min Illumination                          | 0.001 LUX@(F1.2 AGC ON),0LUX with IR               |
| Video Output                              | AHD / TVI / CVI / CVBS (Default: AHD Video Output) |
| Exposure                                  | Brightness/Exposure Mode/Gain                      |
| Coaxial Cable<br>Transmission<br>Distance | 300 m                                              |
| Twisted Cable<br>Transmission<br>Distance | 100 m                                              |
| Language                                  | 10 Kinds of Languages as Chinese/English etc.      |
| O.S.D. Menu                               | UTC Function                                       |
| IR-LED Coverage                           | 18 x Micro IR-LED, around 15M                      |
| Operating<br>Condition                    | Temperature : -20°C~+60°C, Humidity : 90%RH        |
| Power Supply                              | DC 12V ±20%                                        |